ılıılı. cısco

Cisco UCS C4200 Series Rack Server Chassis



The Cisco UCS C4200 Series Rack Server Chassis with the Cisco C125 M5 Rack Server Node delivers outstanding performance for space-constrained environments

Product overview

The Cisco UCS[®] C4200 Series Rack Server Chassis delivers outstanding performance for space-constrained environments. It is among the most versatile general-purpose enterprise infrastructure and application servers in the industry. Supporting up to four Cisco UCS C125 M5 2-socket rack server nodes it delivers industry-leading performance and efficiency for a wide range of workloads, including scale-out/compute intensive, general service provider, and bare-metal applications. The Cisco UCS C-Series Rack Servers can be deployed as standalone servers or as part of the Cisco Unified Computing System[™] (Cisco UCS) to take advantage of Cisco's standards-based unified computing innovations that help reduce customers' Total Cost of Ownership (TCO) and increase their business agility.

The C4200 chassis extends the capabilities of the Cisco UCS portfolio in a 2-Rack-Unit (2RU) form factor supporting up to four Cisco UCS C125 M5 Rack Server Nodes. It incorporates the AMD EPYC 7000 processors, delivering significant performance and efficiency gains in a compact form factor that will improve your application performance while saving space. The C4200 and the C125 M5 nodes deliver outstanding levels of capability and performance in a highly compact package, with:

- · AMD EPYC 7000 series processors, with up to 32 cores per socket
- Up to 2 TB of DRAM using sixteen 128-GB DDR4 DIMMs for 2-socket CPU configuration (eight DIMMs/memory channels per CPU)
- Over 45 TB of storage, with up to six Small-Form-Factor (SFF) 2.5-inch direct-attached drives per node
 - · Either six direct attach SAS/SATA drives or two NVMe plus four SAS/SATA drives
- · Optional dual SD cards or M.2 modular storage for increased storage or boot drive capacity
- Support for the Cisco[®] 12-G 9460-8i PCIe SAS RAID controller with 2-GB Flash-Backed Write Cache (FBWC)
- · OCP 2.0 network mezzanine slot supporting speeds up to 100 Gbps
- Support for Cisco's fourth-generation PCIe Virtual Interface Card (VIC)

Powering next-generation applications

The Cisco UCS C4200 Series Rack Server Chassis is well suited for a wide range of industry-driven workloads in areas such as:

- Research and education
- Aerospace
- Finance
- Manufacturing
- Oil and gas
- Gaming

Management

Cisco provides adaptive management for a new era of IT infrastructure with <u>Cisco Intersight</u>[™]. Cisco Intersight simplifies and automates IT Operations Management (ITOM) to make daily activities easier and more efficient. We have extended our vision of adaptive management to the C4200 platform. You can efficiently implement operations automation of your IT infrastructure from the data center to the edge.

The C125 M5 nodes can be deployed as standalone servers or in a Cisco UCS managed environment. When used in combination with <u>Cisco UCS Manager</u>, the C4200 brings the power and automation of unified computing to enterprise applications, including <u>Cisco SingleConnect technology</u>, drastically reducing switching and cabling requirements.

Cisco UCS Manager uses service profiles, templates, and policy-based management to enable rapid deployment and help ensure deployment consistency. If also enables end-to-end server visibility, management, and control in both virtualized and bare-metal environments.

The Cisco Integrated Management Controller (IMC) delivers comprehensive out-of-band server management with support for many industry standards, including:

- Redfish Version 1.01 (v1.01)
- Intelligent Platform Management Interface (IPMI) v2.0
- Simple Network Management Protocol (SNMP) v2 and v3
- Syslog
- Simple Mail Transfer Protocol (SMTP)
- Key Management Interoperability Protocol (KMIP)
- HTML5 GUI
- HTML5 virtual Keyboard, Video, and Mouse (vKVM)
- Command-Line Interface (CLI)
- XML API management Software Development Kits (SDKs) and DevOps integrations exist for Python, Microsoft PowerShell, Ansible, Puppet, Chef, and more. For more information about integrations, see Cisco DevNet

Product specifications

Table 1, below, lists the specifications for the Cisco UCS C4200 Series Rack Server Chassis and C125 M5 rack server nodes.

 Table 1.
 Product specifications for Cisco UCS C4200 Series Rack Server Chassis and Cisco UCS C125 M5 Rack Server Node

Item	Specification	
Chassis	2RU Cisco UCS C4200 Rack Server Chassis	
Server nodes	Up to four Cisco UCS C125 M5 Rack Server Nodes	
Processors	AMD EPYC 7000 series processors (1 or 2)	
Processor cores	Up to 64 per node	
Memory	16 DDR4 DIMM slots: 16, 32, 64, and 128 GB and up to 2666 MHz per node	
PCIe expansion	1 PCIe 3.0 x 16 slots and 1 PCIe 3.0 x 8 slots, plus one dedicated OCP 2.0 network mezzanine slot per node	
Storage controller	 Internal controllers: Optional Cisco 12-Gbps PCIe RAID Controller (PCIe 3.0) with 2-GB Flash-Backed Write Cache (FBWC), providing enterprise-class data protection for up to six SAS and SATA Hard-Disk Drives (HDDs), or Solid Disk Drives (SSDs) AHCI 6Gbps SATA controller available from CPU 0 supporting up to 6 drives 	
Internal storage	 24 SFF 2.5-inch direct-attach drives Each C125 M5 node has up to six direct- attach 2.5-inch SAS/ SATA HDDs/SSDs or up to two 2.5-inch NVMe drives and four SAS/SATA drives per node 	
Networking	Dedicated OCP 2.0 mezzanine slot that can flexibly accommodate up to 100-Gbps adapters per node Support for PCIe based 4 th Gen VIC Adapters	
Power supplies	Hot-pluggable, redundant 2400W AC	
Other storage	 Dual internal Cisco FlexFlash Secure Digital (SD) cards (32, 64, and 128 GB) for installing an operating system or hypervisor Support for RAID 0 mirroring between SD cards Dedicated Baseboard Management Controller (BMC) MicroSD card (32 GB) for server utilities Dual M.2 SATA SSD 	
Management	Cisco Intersight Cisco IMC <u>Cisco IMC Supervisor</u> Cisco UCS Manager	
Rack options	Cisco ball-bearing rail kit with optional reversible cable management arm	
Physical unit	 2RU high x 32-in. depth High reliability, availability, and serviceability features with easy-to-use latching lid, and hot-swappable and hot-pluggable Nodes, Fans and Storage 	
Hardware and software interoperability	See the Cisco Hardware and Software Interoperability Matrix for a complete listing of supported operating systems and peripheral options	

System requirements

Table 2 lists system requirements for the server.

Table 2.	System requirements
----------	---------------------

Item	Requirements
Cisco UCS Manager (optional)	Release 4.0(1) or Later
Cisco IMC	Release 4.0(1) or Later

Ordering information for Cisco UCS C4200 Series Rack Server Chassis

For information about installing or upgrading your server, see the Cisco UCS C4200 Series Rack Server Chassis hardware installation guide.

For ordering information, see:

<u>Cisco UCS C4200 Series Rack Server Chassis with C125 M5 Rack Server Node specification sheet</u>

Warranty information

Cisco UCS C4200 chassis and Cisco C125 M5 nodes have a three-year Next-Business-Day (NBD) hardware warranty and a 90-day software warranty.

Augmenting the Cisco UCS warranty, Cisco Smart Net Total Care[®] and Cisco Solution Support services are part of Cisco's technical services portfolio. Cisco Smart Net Total Care combines Cisco's industry-leading and awardwinning foundational technical services with an extra level of actionable business intelligence that is delivered to you through the smart capabilities in the Cisco Smart Net Total Care portal. For more information, please refer to <u>https://www.cisco.com/c/en/us/support/services/smart-net-total-care/index.html</u>.

Cisco Solution Support includes both Cisco product support and solution-level support, resolving complex issues in multivendor environments on average 43 percent more quickly than with product support alone. Solution Support is a critical element in data center administration, helping rapidly resolve any issue encountered while maintaining performance, reliability, and return on investment.

This service centralizes support across your multivendor Cisco environment for both our products and our solution partners' products that you have deployed in your IT ecosystem. Whether there is an issue with a Cisco or a solution-partner product, just call us. Our experts are the primary point of contact and own the case from first call to resolution. For more information, please refer to <u>https://www.cisco.com/c/en/us/services/technical/solution-support.html</u>.

Takeback and Recycle Program

https://www.cisco.com/c/en/us/about/product-innovation-stewardship/product-recycling/takebackrecycleprogram.html

Cisco and partner services

Cisco and our industry-leading partners deliver services that accelerate your transition to a Cisco UCS C-Series Rack Servers solution. Cisco Unified Computing Services can help you create an agile infrastructure, accelerate time to value, reduce costs and risks, and maintain availability during deployment and migration. After deployment, our services can help you improve performance, availability, and resiliency as your business needs evolve and help you further mitigate risk. For more information, visit <u>https://www.cisco.com/go/unifiedcomputingservices</u>.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.

Learn more at Cisco Capital Financing at https://www.cisco.com/c/en/us/buy/cisco-capital-finance/overview.html.

For more information

For more information about Cisco UCS servers, refer to https://www.cisco.com/go/ucs.

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA

C78-740839-01 09/18